

Specification		
Video IN		
Camera I/F	Gigabit Ethernet (Camera is required to use specified model)	
Number of Channels	2ch	
Frame Rate	100fps × 1ch (QVGA resolution : 240p)	
	30fps × 1ch (HD resolution : 720p)	
	30fps × 1ch (HD resolution : 720p) * p : progressive	
Analog IN		
Number of Channels	4ch	
Coupling	DC / AC / ICP™(TEDS applicable) Selectable for each ch.	
A/D converter	delta-sigma (simultaneous sampling)	
Bandwidth[Hz]	40k 20k 10k 5k 2.5k 1.25k 630 100	
	96k 48k 24k 12k 6k 3k 1.5k 240 (Bandwidth × 2.4)	
Sampling	Sampling[Hz]	
	40k 20k 10k 5k 2k 1k 500 100	
Frequency	Bandwidth[Hz]	
	Sampling[Hz]	
102.4k 51.2k 25.6k 12.8k 5.12k 2.56k 1.28k 256(Bandwidth × 2.56)		
Analog Output	None	
A/D resolutions	16bit / 24bit selectable	
Input Range	0.01 / 0.0316 / 0.1 / 0.316 / 1 / 2 / 3.16 / 10 [V]	
Dynamic Range	100dB (20kHz bandwidth, 1V range, 24bit mode)	
High Pass Filter	OFF / 5Hz (-12dB/oct)	
Low Pass Filter	OFF / 200 / 500 / 1k / 2k [Hz] (-12dB/oct)	
Absolute maximum input voltage	±50 V	
Inter-channel phase difference	20kHz band and below : within 1 degree 40kHz band and below : within 3 degrees	
ICP™ Current	4mA / 24V	
Digital IN / Pulse IN		
GPS	Position data, Time data	
CAN	All packets data recorded (2 signals monitor available)	
Pulse	1ch (Either Pulse or Ext. Trigger)	
Other		
Video & Analog sync. Accuracy	< +/- 1fps (@ 30fps)	
View while Recording	Video (1ch) / Analog Data / CAN	
Recording START/STOP	Manual mode / Trigger mode	
Trigger	Level, Timer, Repeat, External	
	Pre Trigger, Post Trigger	
Voice Memo	Available	
Recording Media	CFast(up to 64 GB) / SDHC(up to 32 GB) *CFast media is required to record video	
Synchronization	LX-100 series / WX-7000 series, VR-24 x 2	
LCD	5.7 inch	
Operation	Touch Panel + Button	
Dimensions / Weight	W260 x D186 x H77 [mm] / Approx. 2.3[kg]	
Power supply	DC 12 — 16 V	
	AC 100 — 240 V (when using AC adapter)	
Operating conditions	Operating temperature/humidity	0 to 40°C/10 to 80% (no condensation)
	Storage temperature/humidity	-20 to 60°C/5 to 90% (no condensation)
	Operating air pressure	860 — 1060 hPa
	Vibration resistance	MIL-STD-810E Figure 514.4-1, 2, 3

Recording Time (@ CFast 64 GB)

	Camera	Analog * 4ch [hours : minutes]		
		96kHz / 24bit	48kHz / 24bit	24kHz / 24bit
HD(1280x720 / 30fps)	1ch	2:36	2:58	3:08
VGA(640x480 / 30fps)	1ch	4:50	6:16	7:08
	2ch	3:04	3:36	3:52
QVGA(320x240 / 100fps)	1ch	5:16	7:02	8:10
—	—	11:18	24:12	45:48

This table shows approximate times, and record time is different depending on video data.

Accessories

- AC adapter
- Microphone (1 pc.)
- Ear-phone (1 pc.)
- Installation Manual (1 pc.)
- Operation Manual (included in CD)

Options

- Camera Basler ace series (specified model)



- Recording Media CFast / SDHC card



CFast is a flash memory card with the SATA interface which has enhanced format of the Compact Flash, and supports a higher maximum transfer rate.

- Remote Control ER-VRRC



Wired Remote Control Unit ER-VRRC

- Battery unit



Battery unit is attached.
* Battery and Battery Charger are not included.

- Carrying Bag



TEAC AMERICA, INC.

1834 Gage Rd, Montebello, CA 90640
Phone 323.726.0303 | Fax 323.727.7632
Email datarecorder@teac.com
<http://datarecorder.jp/en/>

Other company names and product names in this document are the trademarks or registered trademarks of their respective owners.
Features and specifications are subject to change without notice.
Precaution : To ensure safe handling and operation, read the Instruction Manual before use.



**Records 2ch video, 4ch analog, CAN, GPS and Pulse in perfect sync.
An All-In-One Data Recorder**

There is something you will never be able to analyze using only NVH analog data from the testing field.

TEAC has innovated the analog and video recording technologies that have been used for decades in field testing environments.

The VR-24 is a data recorder that can record traditional video/analog signals along with CAN, GPS and Pulse data simultaneously in perfect sync. Wide bandwidth (40kHz). Because of its small lightweight design with battery operation capability, the VR-24 is an ideal stand-alone data recorder for on-site measurements. These additional data can reveal "hidden details" in your recorded data that you never knew were there.

All-in-one & Stand-alone

An all-in-one unit that records analog, video, CAN, GPS and Pulse data simultaneously in perfect sync.

Portable for field use

Small & lightweight design makes it easier to carry. Superior portability for field use.

*Can be operated on battery power (optional).

Smaller than Letter size

Small footprint
Compact design (W 10 1/4 x D 7 3/8 x H 3 1/8 in)
smaller than letter size

Light Weight

Approximately 5lbs.

Touch panel

Large 5.7 inch touch panel allows intuitive operation.

Wide Bandwidth 40kHz

Fulfill increasing demands for high frequency noise measurements on EV and turbo chargers that are required when downsizing engines.



Display Example

Analog signal can be shown as waveform



Touch panel allows intuitive operation



Analog signal can be shown as bar meter



Recorded video and data can be reviewed on this screen.



For Various Kinds of Automotive Testing
Completed Vehicle Inspection / Claim Investigation / Parts Evaluation / Driving Stability Test, etc.

System configurations

Connected devices and cables are not included with the product.



Synchronized recording is possible with other TEAC data recorders such as WX-7000 and LX-100 series, as well as between two VR-24 units.

For Viewing and Analysis

Optional Software

VR View

Optional VR-View allows you to view signal waveform, video and position data recorded by VR-24, on a single display. Having a way to watch synchronize video and waveforms would greatly help you analyze the phenomena you recorded.

OS supported : Windows 7/ Windows 8 / Windows 8.1

- Waveform display
- CAN signal view
- FFT Analysis
- GPS position data mapping
- Data extracting
- File conversion

Optional accessories

Camera Basler ace series (specified model), Recording media (CFast / SDHC card), Remote Control Unit, Battery Unit, Carrying Bag, GPS receiver